

INDUSTRIAL SHOCK ABSORBERS POWERSTOP

THREAD M16X1.5

► SERIES

PowerStop®




STANDARD ENERGY	HIGH ENERGY	ADJUSTABLE ENERGY
		
The economical	The powerful	The Adjustable

► Material	Stainless steel	► Organic oil (biodegradable)	HEES
► Permitted temperature range	-10 ... +70 [°C]	► H1-certified	Yes
► Angle of Impact max.	2 [°]	► Certifications	LABS / REACH / RoHS
► Max. force at fixed stop	3.5 [kN]		
► Lock nut tightening torque		► Max. absolute pressure	
- Standard energy	15 [Nm]	- Standard energy	1 [bar]
- High Energy	20 [Nm]	- High Energy	10 [bar]
- Adjustable Energy	20 [Nm]	- Adjustable Energy	10 [bar]













► TECHNICAL DATA









	Design	Series	Thread	Stroke variant	Stroke	Hardness degree	Impact velocity		Energy absorption max.			Protection	Reset			Head	Integrated Fix stop	Version
					max.				Continuous operation		Emergency stop operation		Force		Time			
					[mm]		min.	max.	per stroke	per hour	per stroke		min.	max.	max.			
							[m/s]	[m/s]	[J]	[J/h]	[J]		[N]	[N]	[s]			
STANDARD ENERGY	P	SE	16X15	N	12	H - M - S - W	0,1	1,2	20	50.000	20	D - F - A	3	6	0,3	D - E - S - K	x	
							0,8	2,2	20	50.000	20		3	6	0,3		-	
							1,8	3,5	20	50.000	20		3	6	0,3		x	
							3,0	5,0	20	50.000	20		3	6	0,3		x	
HIGH ENERGY	P	HE	16X15	N	12	H - M - S - W	0,1	1,2	34	50.000	42	D - F - A	7	11	0,3	D - E - S - K	x	
							0,8	2,2	32	50.000	38		7	11	0,3		-	
							1,8	3,5	30	50.000	34		7	11	0,3		x	
							3,0	5,0	28	50.000	30		7	11	0,3		x	
ADJUSTABLE ENERGY	P	AE	16X15	N	12	H						D - F - A	7	11	0,3	D - E - S - K	x	
							0,1	5,0	34	50.000	34		7	11	0,3		-	
													7	11	0,3		x	
													7	11	0,3		x	
HIGH ENERGY	P	HE	16X15	L	20	H - M - S - W	0,1	1,2	34	50.000	42	D - A - F	7	11	0,4	D - E - S - K	x	
							0,8	2,2	32	50.000	38		7	11	0,4		-	
							1,8	3,5	30	50.000	34		7	11	0,4		x	
							3,0	5,0	28	50.000	30		7	11	0,4		x	
ADJUSTABLE ENERGY	P	AE	16X15	L	20	H						D - F - A	7	11	0,4	D - E - S - K	x	
							0,1	5,0	34	50.000	34		7	11	0,4		-	
													7	11	0,4		x	
													7	11	0,4		x	

► PROTECTION

no protection	Felt ring	Wiper (NBR)
D -A	F -A	A -A
		
in a clean environment	against dust, chips, ...	against liquid, oil, ...

► TECHNICAL DRAWINGS

	Short piston rod no head	Long piston rod no head	with steel head	with plastic head
	N D -A	N E -A	N S -A	N K -A
STANDARD ENERGY				
HIGH ENERGY				
ADJUSTABLE ENERGY				

	Short piston rod no head	Long piston rod no head	with steel head	with plastic head
	L D -A	L E -A	L S -A	L K -A
HIGH ENERGY				
ADJUSTABLE ENERGY				










INDUSTRIAL SHOCK ABSORBERS POWERSTOP

THREAD M16X1.5

► ACCESSORIES

Pos.	Order no.	Accessories	Remarks
①	PAH16X15-A	Stop sleeve	Including 1x PVM16X15-A. Industrial shock absorber with bellow excluded.
②	PBV16X15ND-A	Side load adapter standard stroke Protection: no protection	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM22X15-A suitable for external thread of the side load adapter.
③	PBV16X15NF-A	Side load adapter standard stroke Protection: felt ring (felt)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM22X15-A suitable for external thread of the side load adapter.
④	PBV16X15NA-A	Side load adapter standard stroke Protection: wiper (NBR)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM22X15-A suitable for external thread of the side load adapter.
⑤	PBV16X15LD-A	Side load adapter long stroke Protection: no protection	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM22X15-A suitable for external thread of the side load adapter.
⑥	PBV16X15LF-A	Side load adapter long stroke Protection: felt ring (felt)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM22X15-A suitable for external thread of the side load adapter.
⑦	PBV16X15LA-A	Side load adapter long stroke Protection: wiper (NBR)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM22X15-A suitable for external thread of the side load adapter.
⑧	PKS16X15-A	Clamping flange orthogonal screwed	Tightening torque of the screws max. 5 Nm.
⑨	PKP16X15-A	Clamping flange screwed in parallel	Tightening torque of the screws max. 3 Nm.
⑩	PVM16X15-A	Stainless steel locknut	Included with the industrial shock absorber.
⑪	PDD16X15-A	Pressure chamber seal	On request. Recommended fixing with PVM16x15-A. Seal must be in full contact on both sides.



► CLASSIFICATION

P **HE** **16X15** **L** **H** **A** **K** **-A**

Design

P Industrial shock absorbers PowerStop

Series

ME Mini Energy

SE Standard Energy

HE High Energy

AE Adjustable Energy

Thread

16 Thread nominal diameter

X

15 Thread pitch (factor 10)

Stroke variant

N Standard stroke

L Long stroke

Hardness degree

H Hard (0.1 - 1.2 m/s; Adjustable Energy: 0.1 - 5 m/s)

M Medium (0.8 - 2.2 m/s)

S Soft (1.8 - 3.5 m/s)

W Supersoft (3 - 5 m/s)

Protection

D no protection

F Felt ring

A Wiper (NBR)

B Bellow (TPE)

Head

D Short piston rod no head

E Long piston rod no head

S with steel head

K with plastic head

Version

-A Versioning from a to z