

INDUSTRIAL SHOCK ABSORBERS POWERSTOP

THREAD M27X3.0

► SERIES

PowerStop®




STANDARD ENERGY	HIGH ENERGY	ADJUSTABLE ENERGY
		
The economical	The powerful	The Adjustable

► Material	Stainless steel	► Organic oil (biodegradable)	HEES
► Permitted temperature range	-10 ... +70 [°C]	► H1-certified	Yes
► Angle of Impact max.	2 [°]	► Certifications	LABS / REACH / RoHS
► Max. force at fixed stop	17 [kN]		
► Lock nut tightening torque		► Max. absolute pressure	
- Standard energy	30 [Nm]	- Standard energy	1 [bar]
- High Energy	60 [Nm]	- High Energy	10 [bar]
- Adjustable Energy	60 [Nm]	- Adjustable Energy	10 [bar]













► TECHNICAL DATA









	Design	Series	Thread	Stroke variant	Stroke	Hardness degree	Impact velocity		Energy absorption max.			Protection	Reset			Head	Integrated Fix stop	Version					
					max. [mm]		min. [m/s]	max. [m/s]	Continuous operation		Emergency stop operation		Force		Time								
									per stroke [J]	per hour [J/h]	per stroke [J]		min. [N]	max. [N]	max. [s]								
STANDARD ENERGY	P	SE	27X30	N	25	H - M - S - W	0,1	1,2	105	120.000	105	D - F - A	11	26	0,4	D - E - S - K	x	-A					
							0,8	2,2	105	120.000	105		11	26	0,4		-						
							1,8	3,5	105	120.000	105		11	26	0,4		x						
							3,0	5,0	105	120.000	105		11	26	0,4		x						
HIGH ENERGY	P	HE	27X30	N	25	H - M - S - W	0,1	1,2	230	120.000	400	D - F - A	26	45	0,4	D - E - S - K	x	-A					
							0,8	2,2	210	120.000	330		26	45	0,4		-						
							1,8	3,5	190	120.000	260		26	45	0,4		x						
							3,0	5,0	170	120.000	190		26	45	0,4		x						
ADJUSTABLE ENERGY	P	AE	27X30	N	25	H	0,1 5,0		230 120.000		230	D - F - A	26	45	0,4	D - E - S - K	x	-A					
													0,1	5,0	230		120.000		230	26	45	0,4	-
													0,1	5,0	230		120.000		230	26	45	0,4	x
													0,1	5,0	230		120.000		230	26	45	0,4	x
HIGH ENERGY	P	HE	27X30	L	40	H - M - S - W	0,1	1,2	230	120.000	400	D - F - A	26	45	0,6	D - E - S - K	x	-A					
							0,8	2,2	210	120.000	330		26	45	0,6		-						
							1,8	3,5	190	120.000	260		26	45	0,6		x						
							3,0	5,0	170	120.000	190		26	45	0,6		x						
ADJUSTABLE ENERGY	P	AE	27X30	L	40	H	0,1 5,0		230 120.000		230	D - F - A	26	45	0,6	D - E - S - K	x	-A					
													0,1	5,0	230		120.000		230	26	45	0,6	-
													0,1	5,0	230		120.000		230	26	45	0,6	x
													0,1	5,0	230		120.000		230	26	45	0,6	x

► PROTECTION

no protection	Felt ring	Wiper (NBR)
D -A	F -A	A -A
		
in a clean environment	against dust, chips, ...	against liquid, oil, ...

► TECHNICAL DRAWINGS

	Short piston rod no head	Long piston rod no head	with steel head	with plastic head
	N D -A	N E -A	N S -A	N K -A
STANDARD ENERGY				
HIGH ENERGY				
ADJUSTABLE ENERGY				

	Short piston rod no head	Long piston rod no head	with steel head	with plastic head
	L D -A	L E -A	L S -A	L K -A
HIGH ENERGY				
ADJUSTABLE ENERGY				










INDUSTRIAL SHOCK ABSORBERS POWERSTOP

THREAD M27X3.0

► ACCESSORIES

Pos.	Order no.	Accessories	Remarks
①	PAH27X30-A	Stop sleeve	Including 1x PVM27X30-A. Industrial shock absorber with bellow excluded.
②	PBV27X30ND-A	Side load adapter standard stroke Protection: no protection	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
③	PBV27X30NF-A	Side load adapter standard stroke Protection: felt ring (felt)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
④	PBV27X30NA-A	Side load adapter standard stroke Protection: wiper (NBR)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑤	PBV27X30LD-A	Side load adapter long stroke Protection: no protection	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑥	PBV27X30LF-A	Side load adapter long stroke Protection: felt ring (felt)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑦	PBV27X30LA-A	Side load adapter long stroke Protection: wiper (NBR)	Impact angle max. 30°. Can only be used in combination with industrial shock absorber without protection and without the Short piston rod no head variant. Lock nut PVM36X15-A suitable for external thread of the side load adapter.
⑧	PKS27X30-A	Clamping flange orthogonal screwed	Tightening torque of the screws max. 22 Nm.
⑨	PKP27X30-A	Clamping flange screwed in parallel	Tightening torque of the screws max. 10 Nm.
⑩	PVM27X30-A	Stainless steel locknut	Included with the industrial shock absorber.
⑪	PDD27X30-A	Pressure chamber seal	On request. Recommended fixing with PVM27x30-A. Seal must be in full contact on both sides.



► CLASSIFICATION

P HE 27X3 L H A K -A

Design

P Industrial shock absorbers PowerStop

Series

ME Mini Energy

SE Standard Energy

HE High Energy

AE Adjustable Energy

Thread

27 Thread nominal diameter

X

30 Thread pitch (factor 10)

Stroke variant

N Standard stroke

L Long stroke

Hardness degree

H Hard (0.1 - 1.2 m/s; Adjustable Energy: 0.1 - 5 m/s)

M Medium (0.8 - 2.2 m/s)

S Soft (1.8 - 3.5 m/s)

W Supersoft (3 - 5 m/s)

Protection

D no protection

F Felt ring

A Wiper (NBR)

B Bellow (TPE)

Head

D Short piston rod no head

E Long piston rod no head

S with steel head

K with plastic head

Version

-A Versioning from a to z